



Fig.1 Mounting Direction(NH-FV Series)

Fig.2 Distance from wall (at mounting direction (II))

Fig.3 Mounting Direction (LA6-5DSNWB-POE)

Fig.4 Distance from wall (at LA6-5DSNWB-POE mounting)

Accessories

指定公差 General Tolerance		角度公差 ±[°] Angular tolerance ±[°]		寸法公差 ±[mm] Dimensional tolerance ±[mm]					図番 Drawing No. NH-WST2-W18		ページ Page 1 / 1	
短辺長さ Length of short side	~	~	100	6	30	120	300	1000	改訂 Rev.	年月日 Date	改訂履歴 Revisions	
精 f	1	0.5	0.3	0.1	中 m	0.1	0.3	0.5	0.7	1		
粗 v	3	1.5	1	0.5	粗 c	0.3	0.5	1	1.2	2		

Specification

Supported Type	NH-FV Series LA6-5DSNWB-POE
Mounting Direction	NH-FV Series : Refer to Fig.1 LA6-5DSNWB-POE : Refer to Fig.3
Mass(Tolerance:±10%)	400g(Accessories not include)
(Remarks) There are no contents of controlled substances exceeding the threshold for the RoHS Directive.	

3	Protective Sheet	1	PET t=0.25	
2	Screw	3	M3X8	
1	Wallmount Bracket	1	SECC Off-white t=2.0	
番号 No.	部品名 Part Name	数量 Qty.	記事 Remarks	
機種 Model	NH-WST2		特注No. S.P.No.	-
図名 Name	Specification			
品目コード Part No.	-	尺度 Scale 1:2	三角法 3rd Angle P.	単位 Unit mm
		株式会社 パトライト PATLITE Corporation		